

# TABLA SELECCION REDUCTOR SW

Reductor	Motor			HP	0,12	0,16	0,25	0,33	0,50	0,75	1,00	1,50	2,00	2,5	3,00	4,00	5,50	7,50	10,00	12,50	15,00	
	A2	A4	A6	Kw	0,09	0,12	0,18	0,25	0,37	0,55	0,75	1,10	1,50	1,8	2,20	3,00	4,00	5,50	7,50	9,20	11,00	
	2800	1400	900																			
<b>5</b>	B5				56-120/9		63-140/11		71-160/14		80-200/19		90-200/24		100/12-250/28		132-300/38		160-350/42			
					63-140/11		71-160/14		80-200/19		90-200/24		100/12-250-28		132-300/38		160-350/42					
					56,0		280,0		180,0													
				SW-030 FA-90/4	1/4																	
				SW-040 FA/RB-110/JC-140, RD-120	1/8																	
				SW-050 FA/RB-125/JC-160, RD-140	2/5																	
				SW-063 FA/RB-180/JC-200, FE-160	2/5																	
				SW-075 FA-200/RB-160	2/8																	
				SW-090 FA/RD-210/RB-250/FC-200	2/5																	
				SW-110 FA-200	4/2																	
			SW-130 FA-320	4/5																		
			SW-150 FA-320	5/0																		



	B14		56-80/9		63-90/11		71-105/14		80-120/19		90-140/24		100/12-160/28	
	HP	Kw	0,12	0,16	0,25	0,33	0,50	0,75	1,00	1,50	2,00	2,5	3,00	4,00
			0,09	0,12	0,19	0,25	0,38	0,56	0,75	1,10	1,50	1,8	2,25	3,00

\* Composición No en stock  
 SW130 y SW150: No en stock  
 ⚠ - Montar casquillo y brida  
 En stock todos los motores hasta 5,5 C)  
 En stock motores 1500 rpm hasta 25 CV  
 Error hasta 5% en velocidades tablas